

GPT.05.153.100/B

Revision: 01



SUZUKI DR 650

ALU-RACK

Montagehinweise

Alle vom Motorrad gelösten Schrauben sind gemäß Herstellerangaben wieder zu montieren, oder mit von SW-MOTECH gelieferten Schrauben zu ersetzen. Falls nicht anderweitig definiert, diese Schrauben nach Tabelle anziehen.

M6	9,6 Nm
M8	23 Nm
M10	46 Nm

Gegebenenfalls Schrauben mit flüssiger Schraubensicherung einkleben.

Prüfen Sie nach 50 km alle Verbindungen auf festen Sitz.

SW-MOTECH GmbH & Co. KG
Ernteweg 8/10
35282 Rauschenberg
Germany

Tel. +49 (0) 64 25/8 16 8-00
Fax +49 (0) 64 25/8 16 8-10

info@sw-motech.com
www.sw-motech.com

ALU-RACK

Mounting Instructions

SW-MOTECH products should be installed by a qualified, experienced motorcycle technician. If you are unsure of your ability to properly install a product, please have the product installed by your local motorcycle dealer. SW-MOTECH takes no responsibility for damages caused by improper installation.

All screws, bolts and nuts, including all replacement hardware provided by SW-MOTECH, should be tightened to the torque specified in the OEM maintenance manual for your motorcycle. If no torque specifications are provided in the OEM maintenance manual, the following torques may be used:

M6	9,6 Nm
M8	23 Nm
M10	46 Nm

All screws, bolts and nuts should be checked after driving the first 50 km to ensure that all are tightened to the proper torque.

Medium strength liquid thread-locker (i.e., "Locktite") should be used to secure all screws, bolts and nuts.

1

ALU-RACK



schwarz/black

GPT.05.153.001/B

Anzahl/Pcs. 1

2

Senkkopfschraube
mit Innensechskant
Countersunk Screw

schwarz/black

M8 x 25 DIN 7991

Anzahl/Pcs. 4

3

Mutter mit Bund,
selbstsichernd
Lock Nut with Flange

schwarz/black

M8 DIN 6927/b

Anzahl/Pcs. 4

4

Montagebrücke vorne
Front Mounting Bridge

GPT.05.153.002

Anzahl/Pcs. 1

5

Innensechskantschraube
Hexagon Socket Screw

M8 x 45 DIN 912

Anzahl/Pcs. 2

6

Distanzbuchse
Spacer

Da:20 Di:8,4 h:4

Anzahl/Pcs. 2

7

Montagebrücke hinten
Rear Mounting Bridge

GPT.05.153.003

Anzahl/Pcs. 1

8

Sechskantschraube
Hexagon Screw

M8 x 35 DIN 933

Anzahl/Pcs. 2

9

Unterlegscheibe
Washer

A 8,4 DIN 125

Anzahl/Pcs. 2

10

Distanzbuchse
Spacer

Da:20 Di:8,4 h:9

Anzahl/Pcs. 2

